

WAXOYL AG

4015 Basel

Date printed 03.03.2017, Revision 03.03.2017

Version 05. Supersedes version: 04

Page 1 / 13

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier****Waxoyl PTFE Spray****1.2 Relevant identified uses of the substance or mixture and uses advised against****1.2.1 Relevant uses**

Lubricant

1.2.2 Uses advised against

None known.

1.3 Details of the supplier of the safety data sheet

Company WAXOYL AG
 Oberwilerstrasse 98
 4015 Basel / SWITZERLAND
 Phone 0041-61-28177 94
 Fax 0041-61-28177 85
 Homepage www.waxoyl.com
 E-mail info@waxoyl.ch

Address enquiries to

Technical information info@waxoyl.ch
Safety Data Sheet sdb@chemiebuero.de

1.4 Emergency telephone number

Advisory body +49 (0)89-19240 (24h) (english)

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture**

Aerosol 1: H222 Extremely flammable aerosol. H229 Pressurised container: May burst if heated.
 Eye Irrit. 2: H319 Causes serious eye irritation.
 STOT SE 3: H336 May cause drowsiness or dizziness.
 Aquatic Chronic 3: H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements**Hazard pictograms****Signal word**

DANGER

Contains:

Acetone

Hazard statements

H222 Extremely flammable aerosol.
 H229 Pressurised container: May burst if heated.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.
 H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P211 Do not spray on an open flame or other ignition source.
 P251 Do not pierce or burn, even after use.
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C / 122°F.
 P280 Wear protective gloves / eye protection / face protection.
 P261 Avoid breathing vapours / spray.
 P312 Call a POISON CENTER / doctor if you feel unwell.
 P337+P313 If eye irritation persists: Get medical advice / attention.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulation.

Special labelling

EUH066 Repeated exposure may cause skin dryness or cracking.

WAXOYL AG

4015 Basel

Date printed 03.03.2017, Revision 03.03.2017

Version 05. Supersedes version: 04

Page 2 / 13

2.3 Other hazards

Environmental hazards

Does not contain any PBT or vPvB substances.

Other hazards

Further hazards were not determined with the current level of knowledge.

SECTION 3: Composition / Information on ingredients

Product-type:

The product is a mixture.

Range [%]	Substance
30 - 40	Acetone
	CAS: 67-64-1, EINECS/ELINCS: 200-662-2, EU-INDEX: 606-001-00-8, Reg-No.: 01-2119471330-49-XXXX
	GHS/CLP: Flam. Liq. 2: H225 - Eye Irrit. 2: H319 - STOT SE 3: H336
20 - 30	iso-Butane
	CAS: 75-28-5, EINECS/ELINCS: 200-857-2, EU-INDEX: 601-004-00-0, Reg-No.: 01-2119485395-27-XXXX
	GHS/CLP: Flam. Gas 1: H220 - Press. Gas: H280
10 - 20	n-Butyl acetate
	CAS: 123-86-4, EINECS/ELINCS: 204-658-1, EU-INDEX: 607-025-00-1, Reg-No.: 01-2119485493-29-XXXX
	GHS/CLP: Flam. Liq. 3: H226 - STOT SE 3: H336
5 - 15	Propane
	CAS: 74-98-6, EINECS/ELINCS: 200-827-9, EU-INDEX: 601-003-00-5, Reg-No.: 01-2119486944-21-XXXX
	GHS/CLP: Flam. Gas 1: H220 - Press. Gas: H280
1 - 5	Hydrocarbons, C9, aromatics
	EINECS/ELINCS: 918-668-5, Reg-No.: 01-2119455851-35-XXXX
	GHS/CLP: Flam. Liq. 3: H226 - STOT SE 3: H335 - Aquatic Chronic 2: H411 - Asp. Tox. 1: H304 - STOT SE 3: H336

Comment on component parts

Substances of Very High Concern - SVHC: substances are not contained or are below 0.1%.
For full text of H-statements: see SECTION 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

Take off contaminated clothing and wash before reuse.

Inhalation

Ensure supply of fresh air.
In the event of symptoms seek medical treatment.

Skin contact

When in contact with the skin, clean with soap and water.
Consult a doctor if skin irritation persists.

Eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists: Get medical advice/attention.

Ingestion

Seek medical advice immediately.

4.2 Most important symptoms and effects, both acute and delayed

Drowsiness
Irritant effects

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

WAXOYL AG

4015 Basel

Date printed 03.03.2017, Revision 03.03.2017

Version 05. Supersedes version: 04

Page 3 / 13

SECTION 5: Fire-fighting measures**5.1 Extinguishing media**

Suitable extinguishing media Foam.
Dry powder.
Water spray jet.
Carbon dioxide.

Extinguishing media that must not be used Full water jet.

5.2 Special hazards arising from the substance or mixture

Risk of formation of toxic pyrolysis products.
Bursting aerosols can be forcibly projected from a fire.

5.3 Advice for firefighters

Use self-contained breathing apparatus.
Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.
Cool containers at risk with water spray jet.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

Keep away from all sources of ignition.
Ensure adequate ventilation.
Use personal protective equipment.

6.2 Environmental precautions

Do not discharge into the drains/surface waters/groundwater.

6.3 Methods and material for containment and cleaning up

Take up mechanically.
Take up residues with absorbent material (e.g. sand).
Dispose of absorbed material in accordance within the regulations.

6.4 Reference to other sections

See SECTION 8+13

SECTION 7: Handling and storage**7.1 Precautions for safe handling**

Use only in well-ventilated areas.
Provide suitable vacuuming at the processing area.
Keep away from all sources of ignition - Refrain from smoking.
Vapours can form an explosive mixture with air.
Do not eat, drink, smoke or take drugs at work.
After worktime and before work breaks the affected skin areas must be thoroughly cleaned.
Use barrier skin cream.
Take off contaminated clothing and wash before reuse.

7.2 Conditions for safe storage, including any incompatibilities

Provide solvent-resistant and impermeable floor.
Prevent penetration into the ground.
Do not store together with oxidizing agents.
Do not store together with food and animal food/diet.
Keep in a cool place, heat causes increase in pressure and risk of bursting.
Keep container in a well-ventilated place.

7.3 Specific end use(s)

See product use, SECTION 1.2

WAXOYL AG

4015 Basel

Date printed 03.03.2017, Revision 03.03.2017

Version 05. Supersedes version: 04

Page 4 / 13

SECTION 8: Exposure controls / personal protection**8.1 Control parameters****Ingredients with occupational exposure limits to be monitored (GB)**

Substance
Acetone
CAS: 67-64-1, EINECS/ELINCS: 200-662-2, EU-INDEX: 606-001-00-8, Reg-No.: 01-2119471330-49-XXXX
Long-term exposure: 500 ppm, 1210 mg/m ³
Short-term exposure (15-minute): 1500 ppm, 3620 mg/m ³
iso-Butane
CAS: 75-28-5, EINECS/ELINCS: 200-857-2, EU-INDEX: 601-004-00-0, Reg-No.: 01-2119485395-27-XXXX
Long-term exposure: 600 ppm, 1450 mg/m ³ , (Butane)
Short-term exposure (15-minute): 750 ppm, 1810 mg/m ³
n-Butyl acetate
CAS: 123-86-4, EINECS/ELINCS: 204-658-1, EU-INDEX: 607-025-00-1, Reg-No.: 01-2119485493-29-XXXX
Long-term exposure: 150 ppm, 724 mg/m ³
Short-term exposure (15-minute): 200 ppm, 966 mg/m ³
Hydrocarbons, C9, aromatics
EINECS/ELINCS: 918-668-5, Reg-No.: 01-2119455851-35-XXXX
Long-term exposure: 100 mg/m ³

Ingredients with occupational exposure limits to be monitored (EU)

Substance / EC LIMIT VALUES
Acetone
CAS: 67-64-1, EINECS/ELINCS: 200-662-2, EU-INDEX: 606-001-00-8, Reg-No.: 01-2119471330-49-XXXX
Eight hours: 500 ppm, 1210 mg/m ³

DNEL

Substance
Hydrocarbons, C9, aromatics
Industrial, inhalative, Long-term - systemic effects: 150 mg/m ³ (lit.).
Industrial, dermal, Long-term - systemic effects: 25 mg/kg bw/day (lit.).
general population, dermal, Long-term - systemic effects: 11 mg/kg bw/day (lit.).
general population, oral, Long-term - systemic effects: 11 mg/kg bw/day (lit.).
general population, inhalative, Long-term - systemic effects: 32 mg/m ³ (lit.).
n-Butyl acetate, CAS: 123-86-4
Industrial, inhalative, Long-term - systemic effects: 480 mg/m ³ .
Industrial, inhalative, Acute - systemic effects: 960 mg/m ³ .
Industrial, inhalative, Long-term - local effects: 480 mg/m ³ .
Industrial, inhalative, Acute - local effects: 960 mg/m ³ .
general population, inhalative, Acute - systemic effects: 859,7 mg/m ³ .
general population, inhalative, Acute - local effects: 859,7 mg/m ³ .
general population, inhalative, Long-term - systemic effects: 102,34 mg/m ³ .
general population, inhalative, Long-term - local effects: 102,34 mg/m ³ .
Acetone, CAS: 67-64-1
Industrial, inhalative, Long-term - local effects: 2420 mg/m ³ .
Industrial, dermal, Long-term - systemic effects: 186 mg/kg bw/d.
Industrial, inhalative, Long-term - systemic effects: 1210 mg/m ³ .
general population, oral, Long-term - systemic effects: 62 mg/kg bw/day.

WAXOYL AG

4015 Basel

Date printed 03.03.2017, Revision 03.03.2017

Version 05. Supersedes version: 04

Page 5 / 13

PNEC	general population, inhalative, Long-term - systemic effects: 200 mg/m ³ .
	general population, dermal, Long-term - systemic effects: 62 mg/kg bw/day.
	Substance
	n-Butyl acetate, CAS: 123-86-4
	soil, 0,0903 mg/kg.
	sediment (seaater), 0,0981 mg/kg.
	sediment (freshwater), 0,981 mg/kg.
	sewage treatment plants (STP), 35,6 mg/l.
	seawater, 0,018 mg/l.
	freshwater, 0,18 mg/l.
	Acetone, CAS: 67-64-1
	soil, 29,5 mg/kg.
	sediment (seaater), 3,04 mg/kg.
	sediment (freshwater), 30,4 mg/kg.
	sewage treatment plants (STP), 100 mg/l.
	seawater, 1,06 mg/l.
	freshwater, 10,6 mg/l.

8.2 Exposure controls

Additional advice on system design	Ensure adequate ventilation on workstation. Measurement methods for taking workplace measurements must meet the performance requirements of DIN EN 482. For example, recommendations are given in the IFA's list of hazardous substances.
Eye protection	Safety glasses. (EN 166:2001)
Hand protection	0,4mm Butyl rubber, >120 min (EN 374-1/-2/-3). The details concerned are recommendations. Please contact the glove supplier for further information.
Skin protection	Protective clothing.
Other	Do not breathe vapour/spray. Avoid contact with eyes and skin. Personal protective equipment should be selected specifically for the working place, depending on concentration and quantity handled. The resistance of this equipment to chemicals should be ascertained with the respective supplier.
Respiratory protection	Breathing apparatus in the event of high concentrations. Short term: filter apparatus, combination filter A-P2. (DIN EN 14387)
Thermal hazards	none
Delimitation and monitoring of the environmental exposition	Comply with applicable environmental regulations limiting discharge to air, water and soil.

WAXOYL AG

4015 Basel

Date printed 03.03.2017, Revision 03.03.2017

Version 05. Supersedes version: 04

Page 6 / 13

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**

Form	aerosol
Color	colourless
Odor	characteristic
Odour threshold	not determined
pH-value	not applicable
pH-value [1%]	not applicable
Boiling point [°C]	not applicable
Flash point [°C]	not applicable
Flammability (solid, gas) [°C]	not applicable
Lower explosion limit	not determined
Upper explosion limit	not determined
Oxidising properties	no
Vapour pressure/gas pressure [kPa]	not determined
Density [g/ml]	0,77 (20 °C / 68,0 °F)
Bulk density [kg/m ³]	not applicable
Solubility in water	immiscible
Partition coefficient [n-octanol/water]	not determined
Viscosity	not applicable
Relative vapour density determined in air	not applicable
Evaporation speed	not applicable
Melting point [°C]	not applicable
Autoignition temperature [°C]	not applicable
Decomposition temperature [°C]	not applicable

9.2 Other information

none

SECTION 10: Stability and reactivity**10.1 Reactivity**

Evolution of flammable mixtures possible in air when heated above flash point and/or during spraying or misting.

10.2 Chemical stability

Stable under normal ambient conditions (ambient temperature).

10.3 Possibility of hazardous reactions

Risk of bursting.

10.4 Conditions to avoid

See SECTION 7.2.

10.5 Incompatible materials

Oxidizing agent

10.6 Hazardous decomposition products

Flammable gases/vapours.

WAXOYL AG

4015 Basel

Date printed 03.03.2017, Revision 03.03.2017

Version 05. Supersedes version: 04

Page 7 / 13

SECTION 11: Toxicological information**11.1 Information on toxicological effects****Acute toxicity**

Product
ATE-mix, inhalative, > 20 mg/l 4h.
ATE-mix, dermal, > 2000 mg/kg.
ATE-mix, oral, > 2000 mg/kg.
Substance
Hydrocarbons, C9, aromatics
LD50, dermal, Rabbit: >2000 mg/kg bw (IUCLID).
LD50, oral, Rat: 3500 mg/kg bw (IUCLID).
LC50, inhalative, Rat: >5,2 mg/L (4h) (IUCLID).
iso-Butane, CAS: 75-28-5
LC50, inhalative, mouse: 1237 mg/l (2h) (Lit.).
Propane, CAS: 74-98-6
LC50, inhalative, Rat: > 1443 mg/l (15 min) (Lit.).
n-Butyl acetate, CAS: 123-86-4
LD50, dermal, Rabbit: >14112 mg/kg (OECD 402).
LD50, oral, Rat: 10760 mg/kg (OECD 423).
LC50, inhalative, Rat: 23.4 mg/l (4h) (OECD 403).
Acetone, CAS: 67-64-1
LD50, dermal, Rabbit: > 15800 mg/kg.
LD50, oral, Rat: 5800 mg/kg (OECD 401).
LC50, inhalative, Rat: 76 mg/l (4h).

Serious eye damage/irritation	Irritant Based on the available information, the classification criteria are fulfilled. Toxicological data of complete product are not available. Calculation method
Skin corrosion/irritation	Does not contain a relevant substance that meets the classification criteria. Based on available data, the classification criteria are not met. Toxicological data of complete product are not available.
Respiratory or skin sensitisation	Does not contain a relevant substance that meets the classification criteria. Based on the available information, the classification criteria are not fulfilled. Toxicological data of complete product are not available.
Specific target organ toxicity — single exposure	Vapours may cause drowsiness and dizziness. Based on the available information, the classification criteria are fulfilled. Toxicological data of complete product are not available. Calculation method
Specific target organ toxicity — repeated exposure	Does not contain a relevant substance that meets the classification criteria. Based on the available information, the classification criteria are not fulfilled. Toxicological data of complete product are not available.
Mutagenicity	Does not contain a relevant substance that meets the classification criteria. Based on the available information, the classification criteria are not fulfilled. Toxicological data of complete product are not available.
Reproduction toxicity	Does not contain a relevant substance that meets the classification criteria. Based on the available information, the classification criteria are not fulfilled. Toxicological data of complete product are not available.
Carcinogenicity	Does not contain a relevant substance that meets the classification criteria. Based on the available information, the classification criteria are not fulfilled. Toxicological data of complete product are not available.
Aspiration hazard	Based on the available information, the classification criteria are not fulfilled.
General remarks	

The determination of properties hazardous to health does not take the propellant or carrier

WAXOYL AG

4015 Basel

Date printed 03.03.2017, Revision 03.03.2017

Version 05. Supersedes version: 04

Page 8 / 13

material into account.

SECTION 12: Ecological information**12.1 Toxicity**

Substance
Hydrocarbons, C9, aromatics
LC50, (96h), Oncorhynchus mykiss: 9,22 mg/L (IUCLID).
EC50, (72h), Selenastrum capricornutum: 19 mg/L (IUCLID).
EC50, (48h), Daphnia magna: 6,14 mg/L (IUCLID).
n-Butyl acetate, CAS: 123-86-4
LC50, (96h), Pimephales promelas: 18 mg/l (OECD 203).
EC50, (72h), Desmodesmus subspicatus: 647.7 mg/l.
EC50, (48h), Daphnia magna: 44 mg/l.
IC50, Bacteria: 356 mg/l (40 h).
NOEC, Desmodesmus subspicatus: 200 mg/l.
Acetone, CAS: 67-64-1
LC50, (48h), Daphnia pulex: 8800 mg/l.
LC50, (96h), Oncorhynchus mykiss: 5540 mg/l.
NOEC, (96h), Algae: 430 mg/l.

12.2 Persistence and degradability

Behaviour in environment compartments	not determined
Behaviour in sewage plant	not determined
Biological degradability	not determined

12.3 Bioaccumulative potential

Accumulation in organisms is not expected.

12.4 Mobility in soil

Spillages may penetrate the soil causing ground water contamination.

12.5 Results of PBT and vPvB assessment

Based on all available information not to be classified as PBT or vPvB respectively.

12.6 Other adverse effects

None known.

WAXOYL AG

4015 Basel

Date printed 03.03.2017, Revision 03.03.2017

Version 05. Supersedes version: 04

Page 9 / 13

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

Waste material must be disposed of in accordance with the Directive on waste 2008/98/EC as well as other national and local regulations. It is not possible to determine a waste code for this product in accordance with the European Waste Catalogue (EWC) since it is only possible to classify it according to how it is used by the customer. The waste code is to be determined within the EU in liaison with the waste-disposal operator.

Product

Dispose of as hazardous waste.

Waste no. (recommended)

160504* gases in pressure containers (including halons) containing dangerous substances

Contaminated packaging

Packaging that cannot be cleaned should be disposed of as for product.
Uncontaminated packaging may be taken for recycling.

Waste no. (recommended)150110*
150104**SECTION 14: Transport information****14.1 UN number**

Transport by land according to
ADR/RID 1950

Inland navigation (ADN) 1950

Marine transport in accordance with
IMDG 1950

Air transport in accordance with IATA 1950

WAXOYL AG


4015 Basel


Date printed 03.03.2017, Revision 03.03.2017


Version 05. Supersedes version: 04


Page 10 / 13

14.2 UN proper shipping name

Transport by land according to ADR/RID	AEROSOLS
- Classification Code	5F
- Label	
- ADR LQ	1 I
- ADR 1.1.3.6 (8.6)	Transport category (tunnel restriction code) 2 (D)

Inland navigation (ADN)	AEROSOLS
- Classification Code	5F
- Label	

Marine transport in accordance with IMDG	Aerosols
- EMS	F-D, S-U
- Label	
- IMDG LQ	1 I

Air transport in accordance with IATA	Aerosols, flammable
- Label	

14.3 Transport hazard class(es)

Transport by land according to ADR/RID	2
Inland navigation (ADN)	2
Marine transport in accordance with IMDG	2.1
Air transport in accordance with IATA	2.1

14.4 Packing group

Transport by land according to ADR/RID	not applicable
Inland navigation (ADN)	not applicable
Marine transport in accordance with IMDG	not applicable
Air transport in accordance with IATA	not applicable

WAXOYL AG

4015 Basel

Date printed 03.03.2017, Revision 03.03.2017

Version 05. Supersedes version: 04

Page 11 / 13

14.5 Environmental hazards

Transport by land according to ADR/RID no

Inland navigation (ADN) no

Marine transport in accordance with IMDG no

Air transport in accordance with IATA no

14.6 Special precautions for user

Relevant information under SECTION 6 to 8.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

not applicable

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

EEC-REGULATIONS 1991/689 (2001/118); 2010/75; 2004/42; 648/2004; 1907/2006 (REACH); 1272/2008; 75/324/EEC (2008/47/EC); (EU) 2015/830; (EU) 2016/131; (EU) 517/2014

TRANSPORT-REGULATIONS DOT-Classification, ADR (2017); IMDG-Code (2017, 38. Amdt.); IATA-DGR (2017).

NATIONAL REGULATIONS (GB): EH40/2005 Workplace exposure limits (Second edition, published December 2011). CHIP 3/ CHIP 4

- **Observe employment restrictions for people** Observe employment restrictions for mothers-to-be and nursing mothers. Observe employment restrictions for young people.

- **VOC (2010/75/CE)** 90%

15.2 Chemical safety assessment

not applicable

SECTION 16: Other information**16.1 Hazard statements (SECTION 03)**

H304 May be fatal if swallowed and enters airways.

H411 Toxic to aquatic life with long lasting effects.

H335 May cause respiratory irritation.

H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H220 Extremely flammable gas.

H336 May cause drowsiness or dizziness.

H319 Causes serious eye irritation.

H225 Highly flammable liquid and vapour.

WAXOYL AG

4015 Basel

Date printed 03.03.2017, Revision 03.03.2017

Version 05. Supersedes version: 04

Page 12 / 13

16.2 Abbreviations and acronyms:

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route
 RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses
 ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure
 ATE = acute toxicity estimate
 CAS = Chemical Abstracts Service
 CLP = Classification, Labelling and Packaging
 DMEL = Derived Minimum Effect Level
 DNEL = Derived No Effect Level
 EC50 = Median effective concentration
 ECB = European Chemicals Bureau
 EEC = European Economic Community
 EINECS = European Inventory of Existing Commercial Chemical Substances
 ELINCS = European List of Notified Chemical Substances
 GHS = Globally Harmonized System of Classification and Labelling of Chemicals
 IATA = International Air Transport Association
 IBC-Code = International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
 IC50 = Inhibition concentration, 50%
 IMDG = International Maritime Code for Dangerous Goods
 IUCLID = International Uniform Chemical Information Database
 LC50 = Lethal concentration, 50%
 LD50 = Median lethal dose
 LC0 = lethal concentration, 0%
 LOAEL = lowest-observed-adverse-effect level
 MARPOL = International Convention for the Prevention of Marine Pollution from Ships
 NOAEL = No Observed Adverse Effect Level
 NOEC = No Observed Effect Concentration
 PBT = Persistent, Bioaccumulative and Toxic substance
 PNEC = Predicted No-Effect Concentration
 REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals
 STP = Sewage Treatment Plant
 TLV@TWA = Threshold limit value – time-weighted average
 TLV@STEL = Threshold limit value – short-time exposure limit
 VOC = Volatile Organic Compounds
 vPvB = very Persistent and very Bioaccumulative

16.3 Other information**Classification procedure**

Aerosol 1: H222 Extremely flammable aerosol. (Bridging principle "Aerosols") H229 Pressurised container: May burst if heated. (Bridging principle "Aerosols")
 Eye Irrit. 2: H319 Causes serious eye irritation. (Calculation method)
 STOT SE 3: H336 May cause drowsiness or dizziness. (Calculation method)
 Aquatic Chronic 3: H412 Harmful to aquatic life with long lasting effects. (Calculation method)

Modified position

SECTION 15 been added: EUH066 Repeated exposure may cause skin dryness or cracking.
 SECTION 2 deleted: environment
 SECTION 2 been added: P501 Dispose of contents/container in accordance with local/regional/national/international regulation.
 SECTION 2 deleted: P271 Use only outdoors or in a well-ventilated area.
 SECTION 2 been added: H412 Harmful to aquatic life with long lasting effects.
 SECTION 2 been added: Aquatic Chronic 3
 SECTION 2 deleted: Asp. Tox. 1
 SECTION 2 deleted: H411 Toxic to aquatic life with long lasting effects.
 SECTION 2 deleted: Aquatic Chronic 2
 SECTION 2 deleted: H315 Causes skin irritation.
 SECTION 2 deleted: Skin Irrit. 2
 SECTION 9 been added: colourless
 SECTION 14 deleted: Aerosols (Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane)

WAXOYL AG

4015 Basel

Date printed 03.03.2017, Revision 03.03.2017

Version 05. Supersedes version: 04

Page 13 / 13



Copyright: Chemiebüro®

