

TBL TRUEGRIP

DESCRIPTION

TBL Truegrip is an additive for **TBL** non-slip coatings which provides improved grip under wet conditions. **TBL Truegrip** comprises accurately sized sand particles with no dust, fines or aggregations.

PRODUCT USES

TBL Truegrip can be added to all versions of **TBL** at a 20 % (m/m) level where wet conditions will be experienced, or where additional non-slip properties are required. Some of the application areas are:

- Load areas of pick-up trucks for protection and non-slip properties
- Floors and steps of transporters and busses
- Ramps for wheelchair access
- Emergency exits and fire escapes
- Non-slip areas around machinery
- Bridges, steps, walkways, decks and helicopter pads on ships
- Non-slip surfaces in showers, change rooms and ablution blocks

ADVANTAGES

TBL Truegrip is easily mixed into **TBL** moisture-cure paints by the end user. As it is reasonably hydrophobic, there is no need to pre-dry the particles or to compensate for thickening with solvent additions.

As the rubber particles in **TBL** non-slip coatings lose some of their non-slip properties when covered with liquids such as water or oil, an addition of **TBL Truegrip** can improve the slip resistance under such conditions.

USEAGE LEVELS

TBL Truegrip is added to **TBL** coatings at a minimum level of 20 %.

USEAGE INSTRUCTIONS

Select the correct size package for either a litre (200 g). Ensure that the Truegrip additive is not noticeably moist, and stir the contents of the package into the paint.

While painting, ensure that the Truegrip particles have not settled by giving it an occasional stir.

TECHNICAL DATA

Pack size:	200 g
Particle size:	325 microns
Shelf life	indefinite
Storage conditions	Cool dry place below 25° C